




Direct Green Laser Diodes

Imagine green laser light directly from a semiconductor. Now it becomes reality.

OSRAM Opto Semiconductors is one of the first worldwide leading suppliers of direct green laser diodes. Mounted in a tiny TO38cut package, the two laser diodes with an optical output power of 30 and 50 milliwatts combine an unbeatable form factor with an excellent beam quality. It also makes them particularly suitable as light sources for projectors, showlasers as well as point and line lasers.



OSRAM
Opto Semiconductors

Direct Green Laser Diodes



Showlaser



Pico projection

Advantages

High-temperature range

Compared to frequency-doubled lasers, direct green lasers have a high operating temperature range of more than 60° C without active cooling. This particular quality makes them ideal for outdoor application.

High beam quality in a small package

With its excellent beam quality, the lasers are well suited for optical imaging of light. In addition, their small package size is particularly advantageous for very compact systems like pico projectors.

High efficiency and long lifetime

Thanks to their good efficiency, the temperature increase of the lasers during operation is minimized. A long lifetime and high reliability at continuous operation is guaranteed.

Applications

Line and dot lasers

Its high temperature stability make direct green lasers the ideal solution for point and line lasers. Unlike red laser light, the green spectrum is the most sensitive to the human eye. To achieve the same laser output, and thus the same laser safety class, green light is perceived more easily by the eye than red light. This means that rangefinders, such as those used by builders, can be used over larger distances.

Direct Green Laser Diodes on the Internet:

www.osram-os.com/green-laser

For further information on the available products, please visit our product catalog at <http://catalog.osram-os.com>

Sales Contacts

Asia

OSRAM Opto Semiconductors Asia Ltd.
30/F China Resources Building
26 Harbour Road, Wan Chai
Hong Kong SAR
Phone: +852 3652 5522
Fax: +852 2802 0880
E-mail: prasia@osram-os.com

Europe

OSRAM Opto Semiconductors GmbH
Leibnizstrasse 4
D-93055 Regensburg, Germany
Phone: +49 941 850 1700
Fax: +49 941 850 3302
E-mail: support@osram-os.com

USA

OSRAM Opto Semiconductors Inc.
1150 Kifer Road, Suite 100
Sunnyvale, CA 94086, USA
Main Phone number: (408) 962-3700
Main Fax: (408) 738-9120
Inbound Toll Free: (866) 993-5211
E-mail: info@osram-os.com

Projection

Direct green laser diodes are an important step toward powerful embedded projectors. The laborious way of producing green light by doubling the frequency of infrared laser is no longer needed. In particular, pico projectors based on MEMS mirror (micro-electromechanical system) will benefit from the small size and the high beam quality of the single mode lasers. The laser diodes produce the right green wavelength for projection and offer a sufficient efficiency of typically 5-6% for battery driven applications.

Showlaser

For show lasers, direct green lasers open up new possibilities as light sources. Their high beam quality enables extremely fine structures to be displayed even over large distances.

Other applications

- Medical applications
- Biotechnology
- Spectroscopy

Technical Data (at 25°C)

Description	PL 520	PL 515
Output Power:	50 mW	30 mW
Emission Wavelength:	515-530 nm	510-530 nm
Operating Temperature	0-60° C	
Typical Threshold Current:	45 mA	50 mA
Typical Operating Current:	150 mA	120 mA
Typical Operating Voltage:	7.0 V	6.7 V
Typical Efficiency:	6%	5%
Package Type:	TO38icut	